# Pan Global Continues Intersecting near Surface Copper-Tin Mineralization at the Escacena Project, Southern Spain and Expands Mineralized Footprint

07.10.2021 | Newsfile

- 19.4m at 1% CuEq, including 11.9m at 1.3% CuEq
- New results confirm continuity and expand the near-surface copper-tin mineralization which remains open in several directions
- Drilling commences on new IP targets to the north

Vancouver, October 7, 2021 - Pan Global Resources Inc. (TSXV: PGZ) (OTC Pink: PGNRF) ("Pan Global" or the "Company") is pleased to announce new high-grade copper and tin intercepts as drilling continues at the La Romana copper/tin target at the Escacena Project. La Romana is located approximately 6km southwest of the former Aznalcollar open pit mine and approximately 15km west of the Las Cruces copper mine, in the Iberian Pyrite Belt, southern Spain.

Tim Moody, Pan Global President and CEO states: "The new drill holes at La Romana confirm additional continuity of the near-surface copper and tin mineralization over a strike of more than 1 km. The mineralization remains wide open to the west towards the La Romana mine workings and down dip. The new results also expand supergene enrichment style copper mineralization in the east with individual assays up to 8.7% Cu in hole LRD69 and supergene copper evident over almost 50m in hole LRD64. Results are awaited for 20 additional drill holes. I'm also very pleased to report that permitting on the adjoining Al Andalus property is imminent. This will provide access to several large gravity targets immediately to the east of La Romana and on the same trend as the Aznalcollar mine."

# Highlights include:

- 19.4m at 1.0% CuEq (0.6% Cu, 0.11% Sn, 3.4g/t Ag) from 45m in drill hole LRD70, including
  - 11.9m at 1.3% CuEq (0.7% Cu, 0.16% Sn, 3.8g/t Ag)
- 19.5m at 0.9% CuEq (0.5% Cu, 0.11% Sn, 2.3g/t Ag) from 21m in LRD68, including
  - 7.5m at 1.2% CuEq (0.7% Cu, 0.15% Sn, 3.6g/t Ag)
- 18m at 0.74% CuEq (0.7% Cu, 3.3g/t Ag) supergene copper from 32m in LRD69, including
  - 5.5m at 1.8% CuEq (1.6% Cu, 8g/t Ag)
- 49m at 0.6% CuEq (0.4% Cu, 0.04% Sn, 2.1g/t Ag) supergene copper from 23m in LRD64, including
  - 4.5m at 1.6% CuEq (1.4% Cu, 0.06% Sn, 3.8g/t Ag) and
  - 3m at 1.1% CuEq (0.8% Cu, 0.05% Sn, 4.1g/t Ag) and
  - 3m at 1.0% CuEq (0.8% Cu, 0.05% Sn, 3.7g/t Ag) and
  - 3m at 1.1% CuEq (0.8% Cu, 0.07% Sn, 3.3g/t Ag)
- 6m at 1.2% CuEq (1.0% Cu, 0.04% Sn, 5g/t Ag) from 139m and 3.15m at 1.6% CuEq (1.3% Cu, 0.03% Sn, 7.5g/t Ag) from 213m in hole LRD84

28.04.2025 Seite 1/7

- 27m at 0.62 CuEq (0.5% Cu, 0.03% Sn, 2.7g/t Ag) from 6m in LRD61, including
  - 3m at 1.3% CuEq (0.9% Cu, 0.08% Sn, 4.3g/t Ag) and
  - 4m at 1.3% CuEq (1.0% Cu, 0.03% Sn, 5.6g/t Ag)

Figure 1 - La Romana geophysics targets and drill hole locations with selected highlights. New drill holes are highlighted in orange.

To view an enhanced version of Figure 1, please visit: https://orders.newsfilecorp.com/files/5190/98783 3ea4e0fbf4e5e8a0 001full.jp

### Drill results

The latest drill results are from twelve new holes in the Phase 4 drill program at the La Romana discovery. The drill program is continuing to test extensions of the copper and tin mineralization in all directions.

Drill holes LRD 61, 64, 68, 69, 70, 72 and 75 targeted up-dip or near-surface mineralization. Holes LRD 71, 73 and 84 tested down-dip extensions. Holes 63 and 66 are located in the footwall to the main copper mineralization.

Drill hole locations are shown in Figure 1 above. Drill hole collar information is provided in Table 1 below. Assay results are summarized in Table 2. The drill holes were all inclined towards the south and all reported drill intervals are approximately true widths.

Table 1 Escacena Project, La Romana drill hole collar information (Total 2195.55m)

Hole ID	Easting <sup>1</sup>	Northing <sup>1</sup>	Azimuth (	(°) Dip (°)	Depth (m)
LRD61	736526	4152629	180	-55	158.2
LRD63	736637	4152541	180	-60	107.25
LRD64	736735	4152595	180	-60	115
LRD66	736786	4152621	180	-55	131.1
LRD68	736235	4152651	180	-55	208
LRD69	736936	4152592	180	-55	103.45
LRD70	736236	4152691	180	-55	176
LRD71	736882	4152920	180	-80	401.5
LRD72	736185	4152672	180	-55	163.8
LRD73	736438	4152763	180	-70	233.8
LRD75	737087	4152663	180	-55	164.25
LRD84	736485	4152800	180	-55	233.2

<sup>&</sup>lt;sup>1</sup> Coordinates are in ERTS89 datum UTM29N

Table 2 - Escacena Project, La Romana drill results summary

Hole	Fr	To	Int	CuEq1	Cu	Sn	Ag	Со	Au	Pb	Zn
			m	%	%	ppm	g/t	ppm	g/t	ppm	ppm
LRD61	6.00	35.00	27.00	0.62	0.47	270	2.7	71	0.01	85	222
	10.00	13.00	3.00	1.28	0.93	825	4.3	104	0.01	19	262
	14.00	18.00	4.00	1.27	1.05	300	5.6	109	0.01	40	244
LRD63	30.30	59.00	28.70	0.34	0.17	294	1.6	78	0.03	354	253
	30.30	39.00	8.70	0.38	0.23	216	2.1	76	0.02	302	279
	30.30	30.80	0.50	1.28	0.97	481	7.1	99	0.03	687	197

28.04.2025 Seite 2/7

```
51.00 53.10 2.10 0.84 0.53 708 1.5 78 0.05 267
                                                         224
      54.00 59.00 5.00 0.39 0.22 353 1.2 57 0.03 265
                                                         223
LRD64 23.00 72.00 49.00 0.60 0.43 376 2.1
                                           67 0.01 134
                                                         403
       23.00 27.50 4.50
                        1.58 1.34 561
                                       3.8
                                           35 0.01 276
                                                         561
      39.00 57.00 18.00 0.71 0.50 448 2.5 72 0.01 122
                                                         519
      43.00 46.00 3.00 1.07 0.82 489 4.1 102 0.01
                                                        1008
      47.00 50.00 3.00 1.01 0.78 462 3.7
                                           71 0.01
                                                    24
                                                         383
      52.00 55.00 3.00 1.09 0.80 683 3.3
                                                         405
                                           70 0.01
                                                    64
LRD66 16.00 103.0087.00 0.24 0.12 189 1.3 62 0.01 127
                                                         330
       16.00 55.00 39.00 0.26 0.16 159 1.4 61 0.01 114
                                                         347
      51.35 51.70 0.35 1.96 1.39 333 14.2 433 0.08 689
                                                        2930
      70.00 71.75 1.75
                       1.40 1.12 327 6.4 155 0.02 101
                                                         386
       71.05 71.75 0.70
                        3.12 2.59 557 14.6 287 0.04 226
                                                         615
LRD68 17.75 42.00 24.25 0.77 0.42 944 2.1
                                           85 0.01
                                                         145
      21.00 40.50 19.50 0.86 0.45 1110 2.3 95 0.01
                                                    80
                                                         152
      33.00 40.50 7.50 1.23 0.691503 3.6 98 0.01
                                                         233
                                                    125
      157.75 158.05 0.30
                        2.60 0.99 4690 8.90 131 0.08
                                                         364
      172.65 172.85 0.20 1.56 1.41 53 3.10 112 0.05
                                                    17
                                                         146
                                                         235
LRD69 25.30 57.00 31.70 0.50 0.43 37
                                       2.3 44 0.01 235
      32.00 50.00 18.00 0.74 0.65 35
                                       3.3
                                           49 0.01
                                                   369
                                                         258
       35.25 40.30 5.05 1.83 1.65 40 8.0 80 0.02 758
                                                         240
       39.00 40.30 1.30 5.14 4.62 113 26.3 184 0.07 2366
                                                        530
LRD70 41.00 73.30 32.30 0.73 0.40 884 2.3 84 0.01
                                                    61
                                                         178
      45.00 64.40 19.40 1.00 0.58 1104 3.4 94 0.01
                                                    87
                                                         221
      52.50 64.40 11.90 1.28 0.70 1614 3.8 114 0.01
                                                    19
                                                         162
      52.50 53.85 1.35 2.36 1.203486 6.6 108 0.01
                                                    46
                                                         130
      61.80 64.40 2.60 2.41 1.492437 8.6 174 0.01
                                                         360
      67.15 67.80 0.65
                       1.52 0.20 4250 1.3 115 0.01
                                                         92
LRD71 179,20 179,55 0.35 0.19 0.09 27
                                      4.9 21 0.02 4060 10300
      293.45293.80 0.35
                        3.75 3.38 71
                                       9.7 269 0.10
                                                    52
                                                         137
      331.50331.90 0.40 2.46 2.16 71
                                      10.5 172 0.06
                                                         216
      363.85364.05 0.20 1.68 1.26 60
                                      7.8 250 0.20 325
                                                         938
      365.00 365.20 0.20 2.51 1.96 63 10.9 362 0.24
                                                         727
LRD72 22.00 53.00 31.00 0.61 0.34 677 2.1 68 0.01
                                                    86
                                                         181
       34.95 48.00 13.05 0.83 0.44 1046 2.4 74 0.01
                                                    57
                                                         152
      34.95 35.15 0.20 4.08 2.62317019.92820.16 299
                                                        1260
       38.50 41.00 2.50
                       1.25 0.67 1627 3.6 94 0.02 22
                                                         114
      38.50 38.80 0.30 5.39 3.47500020.8 199 0.12 121
                                                         174
      43.50 48.00 4.50 1.02 0.541351 3.0 76 0.01 128
                                                         196
      47.50 48.00 0.50 3.63 1.44666013.31430.021040
                                                         369
      52.00 53.00 1.00 1.26 0.552130 2.3 93 0.02 98
                                                         159
LRD73117.00127.0010.00 0.51 0.36 289 2.2 63 0.01 142
                                                         594
      122.00 126.00 4.00 0.80 0.58 446 3.6 70 0.01 226
      207.60 208.70 1.10 0.59 0.04 119 12.1 78 0.37 7010 7850
LRD75 105.00 115.00 10.00 0.13 0.05 31
                                       2.8 37 0.02 2884 5431
      105.00 105.40 0.40 1.45 0.71 37 22.4 485 0.23 4450 11650
      112.00 112.85 0.85 0.20 0.09 41
                                       3.9 30 0.04 4500 11800
LRD84 82.40 84.50 2.10
                        0.56 0.30 62
                                      9.9
                                           67 0.09 2275 5821
      83.25 84.10 0.85 0.88 0.48 73 15.4 85 0.16 233011000
      139.00 145.00 6.00
                       1.23 1.00 384 5.0 95 0.01 109
                                                         603
      141.05 143.50 2.45 2.63 2.20 739 10.0 146 0.01
                                                         596
      141.05 142.45 1.40 4.19 3.50 1267 15.8 210 0.02
                                                         802
                                                   43
      207.00208.00 1.00 2.13 0.017090 0.6 70 0.02 51
                                                         315
                       1.58 1.27 290 7.5 146 0.06 964 2191
      213.00216.15 3.15
      213.85 215.45 1.60 2.56 2.15 369 10.3 199 0.08 914 2163
```

28.04.2025 Seite 3/7

<sup>&</sup>lt;sup>1</sup> Metal prices used: Copper US\$6,200 per tonne, Silver USD22.50 per ounce, Gold US\$1,500 per ounce,

Cobalt US\$32,800 per tonne and Tin US\$18,000 per tonne. The copper equivalent (CuEq ) values are for exploration purposes only and include no assumptions for metal recovery.

The results add to the near-surface copper and tin mineralization, with copper mineralization remaining open along strike to the west and down-dip. Additional supergene enrichment style copper mineralization was intersected in the east. The latest drill results confirm the continuity of the near-surface high-grade copper and tin mineralization extending over a strike of more than 1 km.

The primary mineralization includes mainly stockwork, semi-massive sulphides and bands of massive sulphide, with chalcopyrite as the main primary copper mineral and cassiterite as the only observed tin mineral. The copper mineralization is also associated with elevated levels of silver, cobalt and gold. A metal zonation is also apparent, progressing from copper and tin in the west to copper and then zinc in the east.

Drill hole LRD61 extends the near-surface copper mineralization approx. 25m up-dip to the south of hole LRD24. The hole commenced in 0.15% Cu from surface. Results include:

- 27m at 0.6% CuEq (0.5% Cu, 0.03% Sn, 2.7g/t Ag) from 6m downhole, including
  - 3m at 1.3% CuEq (0.9% Cu, 0.08% Sn, 4.3g/t Ag, 104ppm Co), and
  - 4m at 1.3% CuEq (1.0% Cu, 0.03% Sn, 5.6g/t Ag, 109ppm Co)

Drill hole LRD63 intersected a broad zone of weakly anomalous copper, tin and silver in the largely pyritic footwall to the main copper zone. Results include:

- 28.7m at 0.2% Cu, 0.03% Sn, 1.6g/t Ag from 30.3m, including
  - 0.5m at 1.3% CuEq (1.0% Cu, 0.05% Sn, 7.1g/t Ag)

Drill hole LRD64 extends the near-surface copper approx. 25m south of hole LRD55 and intersected a 49m-wide supergene copper zone commencing immediately beneath the cover sediments with several intervals of higher-grade supergene enrichment style mineralization. Results include:

- 49m at 0.6% CuEq (0.43% Cu, 0.04% Sn, 2.1g/t Ag) from 23m, including
  - 4.5m at 1.6% CuEq (1.3% Cu, 0.06% Sn, 3.8g/t Ag)
  - 3m at 1.1% CuEq (0.8% Cu, 0.05% Sn, 4.1g/t Ag)
  - 3m at 1.0% CuEq (0.8% Cu, 0.05% Sn, 3.7g/t Ag)
  - 3m at 1.1% CuEq (0.8% Cu, 0.07% Sn, 3.3g/t Ag)

Drill hole LRD66 drilled a thick zone pyritic footwall zone anomalous in copper and tin (87m at 0.12% Cu, 0.02% Sn, 1.3g/t Ag) with only narrow high-grade intercepts, including

- 0.35m at 2.0% CuEq (1.4% Cu, 0.03% Sn, 14.2g/t Ag) from 51.35m
- 0.7m at 3.1% CuEq (2.6% Cu, 0.06% Sn, 14.6g/t Ag) from 71.05m

Drill hole LRD68 extends the near surface copper and tin mineralization up-dip in the west and shows tin increasing in this direction (individual assays up to 4.7% Cu, 0.92% Sn and 22g/t Ag). Results include:

- 19.5m at 0.9% CuEq (0.5% Cu, 0.11% Sn, 2.3g/t Ag) from 21m, including
  - 7.5m at 1.2% CuEq (0.7% Cu, 0.15% Sn, 3.6g/t Ag)

Drill hole LRD69 extends the near-surface supergene enrichment-style copper mineralization approx. 50m west of hole LRD58 which intersected 14.7m at 1.4% CuEq. The hole intersected approximately 30m of

28.04.2025 Seite 4/7

supergene chalcocite mineralization from 25m down-hole with individual assay values up to 8.7% Cu, 53g/t Ag and 0.13g/t Au. The hole commenced in copper mineralization from immediately beneath the cover sediments at 25m down-hole. Results include:

- 18m at 0.74% CuEq (0.7% Cu, 3.3g/t Ag) from 32m, including
  - 5.1m at 1.8% CuEq (1.6% Cu, 8g/t Ag), including
    - 1.3m at 5.1% CuEq (4.6% Cu, 26.3g/t Ag)

Drill hole LRD70 extends the near-surface copper-tin mineralization in the west approx. 30m down-dip from hole LRD68 and shows improving grade and thickness, including high tin values (assays up to 4.7% Cu, 0.94% Sn and 26g/t Ag). Results include:

- 19.4m at 1.0% CuEq (0.6% Cu, 0.11% Sn, 3.4g/t Ag) from 45m, including
  - 11.9m at 1.3% CuEq (0.7% Cu, 0.16% Sn, 3.8g/t Ag), including
    - 1.35m at 2.4% CuEq (1.2% Cu, 0.35% Sn, 6.6g/t Ag)
    - 2.6m at 2.4% CuEq (1.5% Cu, 0.24% Sn, 8.6g/t Ag)

Drill hole LRD71 indicates the high-grade massive chalcopyrite mineralization in previous drill holes LRD19 and LRD22 remains open but thins in this area. A narrow band of lead/zinc mineralization in the hanging wall is also present indicating continuity with the adjacent drill holes. Results include:

- 0.35m at 0.4% Cu, 1.03% Zn, 0,41% Pb, 0.09% Sn, 2.3g/t Ag from 179.2m
- 0.35m at 3.8% CuEq (3.4% Cu, 9.7g/t Ag, 0.10g/t Au) from 293.45m
- 0.4m at 2.5% CuEq (2.2% Cu, 10.5g/t Ag) from 331.9m
- 0.2m at 1.7% CuEq (1.3% Cu, 7.8g/t Ag, 0.2g/t Au) from 363.85m
- 0.2m at 2.5% CuEq (2.0% Cu, 10.9g/t Ag, 0.24g/t Au, 0.04% Co) from 365m

Drill hole LRD72 extends the near-surface copper/tin mineralization 50m to the east of hole LRD68, with assay values up to 3.47% Cu, 0.67% Sn, 20.8g/t Ag and 0.16g/t Au. Results include:

- 31m at 0.6% CuEq (0.3% Cu, 0.07% Sn, 2.1g/t Ag) from 22m, including
  - 0.25m at 4.1% CuEq (2.6% Cu, 0.32% Sn, 19.9g/t Ag, 0.16g/t Au)
  - 2.5m at 1.3% CuEq (0.7% Cu, 0.16% Sn, 3.6g/t Ag), includes
    - 0.3m at 5.4% CuEq (3.5% Cu, 0.5% Sn, 20.8g/t Ag, 0.12g/t Au)
  - 4.5m at 1.0% CuEq (0.5% Cu, 0.14% Sn, 3g/t Ag), includes
    - 0.5m at 3.6% CuEq (1.4% Cu, 0.67% Sn, 13.3g/t Ag)
  - 1.0m at 1.3% CuEq (0.6% Cu, 0.21% Sn, 2.3g/t Ag) from 52m

Drill hole LRD73 intersected weak copper mineralization approx. 50m down-dip from hole LRD6. Higher copper grades in adjacent drill holes to the east and west indicate the copper/tin mineralization remains open down-dip. A narrow polymetallic interval was also intercepted much deeper in the footwall. Results include:

- 10m at 0.5% CuEq (0.4% Cu, 0.03% Sn, 2.2g/t Ag) from 117m; and
- 1.1m at 0.70% Pb, 0.79% Zn, 12.1g/t Ag, 0.37g/t Au) from 207.6

Drill hole LRD75 shows copper decreasing and lead/zinc increasing in the far east, suggesting a halo to the

28.04.2025 Seite 5/7

main copper mineralization. A deep IP anomaly indicates the copper mineralization potentially remains open at depth towards the east. Results include:

- 10m at 0.05% Cu, 0.29% Pb, 0.54% Zn, 2.8g/t Ag from 105m, including
- 0.4m at 0.7% Cu, 0.45% Pb, 1.17% Zn, 22.4g/t Ag, 0.23g/t Au) and
- 0.85m at 0.09% Cu, 0.45% Pb, 1.18% Zn, 3.9g/t Ag

Drill hole LRD84 intersected a narrow polymetallic interval in the hanging wall above two deeper copper intervals, each containing higher grade copper intercepts showing the copper mineralization remains open down-dip . Results include:

- 2.1m at 0.6% CuEg (0.3% Cu, 9.9g/t Ag), 0.23% Pb, 0.58% Zn from 82.4m, including
  - 0.85m at 0.9% CuEq (0.5% Cu, 15.4g/t Ag, 0.16g/t Au), 0.23% Pb, 1.1% Zn
- 6m at 1.2% CuEq (1.0% Cu, 0.04% Sn, 5.0g/t Ag) from 139m, including
  - 2.45m at 2.6% CuEq (2.2% Cu, 0.07% Sn, 10g/t Ag), includes
    - 1.4m at 4.2% CuEq (3.5% Cu, 0.13% Sn, 15.8g/t Ag)
- 3.15m at 1.6% CuEq (1.3% Cu, 0.03% Sn, 7.5g/t Ag) from 213m, including
  - 1.6m at 2.6% CuEq (2.2% Cu, 0.04% Sn, 10.3g/t Ag)

Assay results are pending for an additional 20 completed drill holes. The Phase 4 drill program will continue to the west towards the La Romana mine workings pending access. Preparations are underway to test Induced Polarity (IP) chargeability targets immediately north of La Romana.

# QA/QC

Core size was HQ (63mm) and all samples were ½ core. Nominal sample size was 1m core length and ranged from 0.4 to 2m. Sample intervals were defined using geological contacts with the start and end of each sample physically marked on the core. Diamond blade core cutting and sampling was supervised at all times by Company staff. Duplicate samples of ¼ core were taken approximately every 30 samples and Certified Reference materials inserted every 25 samples in each batch.

Samples were delivered to ALS laboratory in Seville, Spain and assayed at the ALS laboratory in Ireland. All samples were crushed and split (method CRU-31, SPL22Y), and pulverized using (method PUL-31). Gold analysis was by 50gm Fire assay with ICP finish (method Au-ICP22) and multi element analysis was undertaken using a 4-acid digest with ICP AES finish (method ME-ICP61). Tin was analysed in selected intervals using Lithium borate fusion and ICP MS finish (method ME-MS81). Over grade base metal results were assayed using a 4-acid digest ICP AES (method OG-62). Over grade tin was determined using peroxide fusion with ICP finish (method Sn-ICP81x).

# **Qualified Person**

Patrick Downey, a Director of Pan Global Resources and a qualified person as defined by National Instrument 43-101, has reviewed the scientific and technical information that forms the basis for this news release. Mr. Downey is not independent of the Company.

### About Pan Global Resources

<u>Pan Global Resources Inc.</u> is actively engaged in base and precious metal exploration in southern Spain and is pursuing opportunities from exploration through to mine development. The Company is committed to operating safely and with respect to the communities and environment where we operate.

On behalf of the Board of Directors www.panglobalresources.com

# FOR FURTHER INFORMATION PLEASE CONTACT:

28.04.2025 Seite 6/7

## info@panglobalresources.com

Statements which are not purely historical are forward-looking statements, including any statements regarding beliefs, plans, expectations or intentions regarding the future. It is important to note that actual outcomes and the Company's actual results could differ materially from those in such forward-looking statements. The Company believes that the expectations reflected in the forward-looking information included in this news release are reasonable but no assurance can be given that these expectations will prove to be correct and such forward-looking information should not be unduly relied upon. Risks and uncertainties include, but are not limited to, economic, competitive, governmental, environmental and technological factors that may affect the Company's operations, markets, products and prices. Readers should refer to the risk disclosures outlined in the Company's Management Discussion and Analysis of its audited financial statements filed with the British Columbia Securities Commission.

The forward-looking information contained in this news release is based on information available to the Company as of the date of this news release. Except as required under applicable securities legislation, the Company does not intend, and does not assume any obligation, to update this forward-looking information.

NEITHER TSX VENTURE EXCHANGE NOR ITS REGULATION SERVICES PROVIDER (AS THAT TERM IS DEFINED IN THE POLICIES OF THE TSX VENTURE EXCHANGE) ACCEPTS RESPONSIBILITY FOR THE ADEQUACY OR ACCURACY OF THIS RELEASE.

To view the source version of this press release, please visit https://www.newsfilecorp.com/release/98783

Dieser Artikel stammt von Rohstoff-Welt.de Die URL für diesen Artikel lautet:

https://www.rohstoff-welt.de/news/395996--Pan-Global-Continues-Intersecting-near-Surface-Copper-Tin-Mineralization-at-the-Escacena-Project-Southern-Spa

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches Meinungsbild darstellen. Direkte oder indirekte Aussagen in einem Beitrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere AGB/Disclaimer!

Die Reproduktion, Modifikation oder Verwendung der Inhalte ganz oder teilweise ohne schriftliche Genehmigung ist untersagt! Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt.de -1999-2025. Es gelten unsere AGB und Datenschutzrichtlinen.

28.04.2025 Seite 7/7