Bravo's Trenching Program Continues to Expand Oxide PGM+Au Mineralization

16.10.2024 | CNW

Highlights include 112m at 1.19g/t PGM+Au, including 16m at 2.76g/t PGM+Au and, 156m at 1.01g/t PGM+Au, including 5.24g/t PGM+Au

VANCOUVER, Oct. 16, 2024 - <u>Bravo Mining Corp.</u> (TSXV: BRVO) (OTCQX: BRVMF), ("Bravo" or the "Company") is please report that it has received assay results from eight trenches in the Central and North Sectors at its 100% owned Luanga palladium + platinum + rhodium + gold + nickel project ("Luanga" or "Luanga PGM+Au+Ni Project"), located in the World Carajás Mineral Province, state of Pará, Brazil.

"Trenching has uncovered a wider lateral extent of oxide PGM+Au mineralization at surface, which includes areas with grades. These findings suggest a potential increase in the volume of oxide mineralization at Luanga. Additionally, the higher-grade zones within these sections align with or enhance the grades observed in the drilling below the trench line supporting our interpretation of supergene enrichment," said Luis Azevedo, Chairman and CEO of Bravo.

Highlights Include:

- Trenching across the strike of the Luanga PGM+Au+Ni deposit continues to be successful, with work to date almost complete in the North and Central Sectors. Results highlight significant expansion in the lateral extent of shallow mineralization, which extends across the topographic highs, along the entire 8.1km strike length of the Luanga detested to date.
- Results confirm the presence of enrichment in the saprolite zone, while encountering grades that are on par or be the grade of the oxide mineralization and often improve upon intersections encountered by drilling in the underlying rock.
- In the North Sector, trench TRC24LU043, where more pronounced topography again provides clearer evidence of supergene enrichment, returned 156.5m @ 1.01g/t PGM+Au, including 5m @ 5.24g/t PGM+Au.
- This "mushrooming" of oxide mineralization in the supergene zone demonstrates the potential for volumetric grov future volumes of oxide mineralization.
- Drilling continues at the T5 target, with assays pending for six drill holes, all of which have all intersected copper mineralization on the eastern end of T5.

TRENCH-ID	From	10	Width	Pd	Pt	Rh	Au (g/t)	PGM + A (g/t)	u I YPE
	(m)	(m)	(m)	(g/t)	(g/t)	(g/t)			
TRC24LU030	51.25	249.45	198.20	0.48	0.22	0.03	0.08	0.81	Ox
TRC24LU031E	3 17.40	129.75	112.35	0.69	0.40	0.03	0.07	1.19	Ox
Including	39.50	56.10	16.60	1.79	0.70	0.12	0.16	2.76	Ox
TRC24LU032	216.30	329.85	113.55	0.69	0.38	0.02	0.02	1.12	Ox
TRC24LU043	30.15	186.65	156.50	0.56	0.37	0.06	0.02	1.01	Ox
Including	38.00	43.00	5.00	2.87	2.00	0.28	0.09	5.24	Ox

Notes: All 'From', 'To' depths, and 'Thicknesses' are along the topographic surface.

Type: Ox = Oxide. Recovery methods and results will differ based on the type of mineralization.

Luanga Trenching Program

Trenching across the strike of the Luanga PGM+Au+Ni deposit aims to improve the interpretation of near surface mine

19.04.2025 Seite 1/5

and to reduce the distance/spacing between assay data points with the objective of supporting mineral resource classif the indicated category. The program continues to be successful in meeting Bravo's objectives, with trenching almost cothe North and Central Sectors and only eight trenches remaining to be completed this year.

Trenches TRC24LU030, 031A+B, 032, 035 and 036 (Figure 1) cover the southern extent of the Central Sector, while tr TRC24LU043 and 044 are at the southern extent of the North Sector. Trenching continues in the Central Sector, with o trench to complete before commencing in the Southwest Sector. Figure 3 shows the location of trenches in the Central reported in this news release.

Trenching results continue to highlight significant expansion in the lateral extent of shallow oxide mineralization, which across the topographically elevated areas, along the entire 8.1km strike length of the Luanga PGM+Au deposit. Results continue to confirm the presence of enrichment in the saprolite zone (above the base of oxidation), but to lesser degree Central Sector where the topographic highs are less exaggerated (see the plan view in Figure 1 and Section 1 in Figure encountering grades that are equal or better than average grades of oxide mineralization in surrounding drill holes. In the Sector, trench TRC24LU043, where more pronounced topography demonstrates clearer evidence of supergene enrichment a result of 156m @ 1.01g/t PGM+Au, including 5m @ 5.24g/t PGM+Au.

Figure 2 (Section 1) illustrates the extent of surface oxide mineralization compared to underlying narrower zones of prir (fresh rock) mineralization observed in drilling below the trench. This "mushrooming" of oxide mineralization in the super zone demonstrates the potential for volumetric growth in future oxide mineralization that it was not possible to define by alone

Trenching continues along the entire 8.1km strike length of the Luanga deposit, with work finalizing the Central Sector progressing to completion in the Southwest Sector.

The same sampling, assay laboratory procedures and QAQC protocols as applied to drill core sampling are applied to tamples.

Luanga Drilling & Trenching Status

A total of 332 drill holes have been completed by Bravo to date, for 70,577.75 metres, including eight metallurgical hole subject to routine assaying). Results have been reported for 267 Bravo drill holes to date. Assay results for 57 Bravo drill have been completed are currently outstanding (excluding the metallurgical holes). A total of 37 trenches have been completed to date (for 7,623.08 metres), with results for 36 trenches reported and results for 1 trench pending.

T5 Target - Exploration Update

Drilling continues at the T5 target, located 1km east of the Luanga PGM+Au Deposit. Assays are pending for drill holes DDH2405T012, 013, 014, 015, 016, and 017, all of which have intersected copper sulphide mineralization on the easter T5.

Complete Table of Recent Intercepts - Trenching

19.04.2025 Seite 2/5

TRENCH-ID	From	То	Thickness (m)	Pd	Pt	Rh	Au (g/t)	PGM + Au (g/t)	TYPE
	(m)	(m)		(g/t)	(g/t)	(g/t)			
TRC24LU030	8.00	15.00	7.00	0.49	0.18	0.01	0.07	0.74	Ox
And	22.65	34.65	12.00	0.56	0.17	0.01	0.11	0.85	Ox
And	51.25	249.45	198.20	0.48	0.22	0.03	0.08	0.81	Ox
Including	159.45	328.20	68.75	0.24	0.22	0.01	0.01	0.48	Ox
TRC24LU031	36.10	51.50	15.40	0.48	0.19	<0.01	0.29	0.97	Ox
And	127.00	133.00	6.00	0.30	0.13	80.0	0.11	0.62	Ox
TRC24LU031E	30.00	4.50	4.50	0.34	0.15	0.07	0.27	0.83	Ox
And	17.40	129.75	112.35	0.69	0.40	0.03	0.07	1.19	Ox
Including	39.50	56.10	16.60	1.79	0.70	0.12	0.16	2.76	Ox
And	135.75	5 171.40	35.65	0.23	0.38	0.04	0.03	0.68	Ox
And	182.40	205.40	23.00	0.24	0.64	0.03	0.01	0.92	Ox
TRC24LU032	88.20	91.20	3.00	0.63	0.34	<0.01	0.06	1.03	Ox
And	124.60	141.60	17.00	0.32	0.10	0.01	0.12	0.54	Ox
And	145.6	149.60	4.00	0.50	0.22	0.03	0.04	0.79	Ox
And	'65.60	199.30	33.70	0.55	0.22	0.04	0.12	0.93	Ox
And	216.30	329.85	113.55	0.69	0.38	0.02	0.02	1.12	Ox
TRC24LU035	86.10	100.60	14.50	0.24	0.13	0.02	0.12	0.51	Ox
And	108.60	112.60	4.00	0.21	0.12	0.02	0.05	0.40	Ox
And	116.05	5 135.75	519.70	0.41	0.18	0.02	0.02	0.62	Ox
And	139.75	5 178.95	39.20	0.61	0.22	0.02	0.01	0.86	Ox
TRC24LU036	No Sig	gnificant	Result						
TRC24LU043	30.15	186.65	156.50	0.56	0.37	0.06	0.02	1.01	Ox
Including	38.00	43.00	5.00	2.87	2.00	0.28	0.09	5.24	Ox
TRC23LU044	8.60	75.20	66.60	0.58	0.34	0.06	0.08	1.06	Ox
And	152.05	5 182.25	30.20	0.71	0.23	0.07	0.02	1.03	Ox

Notes: All 'From', 'To' depths, and 'Thicknesses' are along the topographic surface.

Type: Ox = Oxide. FR = Fresh Rock. Recovery methods and results will differ based on the type of mineralization.

About Bravo Mining Corp.

Bravo is a Canadian and Brazil-based mineral exploration and development company focused on advancing its PGM and copper-gold Luanga Project in the world-class Carajás Mineral Province, Para State, Brazil.

19.04.2025 Seite 3/5

Bravo is one of the most active explorers in Carajás. The team, comprising of local and international geologists, has a proven track record of PGM, nickel, and copper discoveries in the region. They have successfully taken a past IOCG greenfield project from discovery to development and production in the Carajás.

The Luanga Project is situated on mature freehold farming land and benefits from being located close to operating mines and a mining-experienced workforce, with excellent access and proximity to existing infrastructure, including road, rail, and hydro grid power. A fully funded +70,000m infill, step out and exploration drilling and trenching program is well advanced for 2024. Bravo's current Environmental, Social and Governance activities includes planting more than 30,000 trees in and around the Project area, hiring and contracting locally, and working to ensure protection of the environment during its exploration activities.

Technical Disclosure

Technical information in this news release has been reviewed and approved by Simon Mottram, F.AusIMM (Fellow Australia Institute of Mining and Metallurgy), President of Bravo Mining Corp. who serves as the Company's "qualified person" as defined in National Instrument 43-101 Standards of Disclosure for Mineral Projects ("NI 43-101"). Mr. Mottram has verified the technical data and opinions contained in this news release.

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

Forward Looking Statements

This news release contains forward-looking information which is not comprised of historical facts. Forward-looking information is characterized by words such as "Expand", "significant", "greater", "high-grade", "validate", "improve", "enrichment", "successful", "expansion", "clearer evidence", "potential", "growth", "aims", "highlight", "better", variants of these words and other similar words, phrases, or statements that certain events or conditions "may", "should" or "will" occur. This news release contains forward-looking information pertaining to the Company's ongoing trenching program; the interpretation of the results of trench data, including that the mineralization thickens in the saprolite, is locally supergene enriched, and the impact on future mineral resource estimates thereof; the potential that similar thickening and supergene enrichment may be present along the entire strike length of the Luanga deposit and the impact on mineral resource estimates thereafter; the potential future economics of the saprolite material, including the recoverability of PGMs and Au therein; the results of planned additional trenching; and the Company's plans in respect thereof. Forward-looking information involves risks, uncertainties and other factors that could cause actual events, results, and opportunities to differ materially from those expressed or implied by such forward-looking information. Factors that could cause actual results to differ materially from such forward-looking information include, but are not limited to, unexpected results from exploration programs, changes in the state of equity and debt markets, fluctuations in commodity prices, delays in obtaining required regulatory or governmental approvals, environmental risks, limitations on insurance coverage; and other risks and uncertainties involved in the mineral exploration and development industry. Forward-looking information in this news release is based on the opinions and assumptions of management considered reasonable as of the date hereof, including, but not limited to results from trenching reasonably reflect consistent zones of oxide mineralization and that future results from additional trenching will continue to see similar broad distribution of oxides with higher grades that the current MRE; that activities will not be adversely disrupted or impeded by regulatory, political, community, economic, environmental and/or healthy and safety risks; that the Luanga Project will not be materially affected by potential supply chain disruptions; and general business and economic conditions will not change in a materially adverse manner. Although the Company believes that the assumptions and factors used in preparing the forward-looking information in this news release are reasonable, undue reliance should not be placed on such information. The Company disclaims any intention or obligation to update or revise any forward-looking information, other than as required by applicable securities laws.

Schedule 1: Trench Location Details

19.04.2025 Seite 4/5

HOLE-ID	Compan	y East (m)	North (m)	RL (m)	Datum	Length (m	ı) Azimuth	Dip Sector
TRC23LU030	Bravo	658585.030	9340680.41	329.000	SIRGAS2000_UTN	1_22\$ 330.45	330.00	0.00 Central
TRC24LU031A	A Bravo	658492.930	9340644.18	0 284.250	SIRGAS2000_UTN	1_22S 133.00	330.00	0.00 Central
TRC24LU031E	3 Bravo	658429.546	9340753.90	2 257.074	4SIRGAS2000_UTN	1_22S 205.40	330.00	0.00 Central
TRC24LU032	Bravo	658455.67	1 9340506.29	4284.139	SIRGAS2000_UTN	1_22S 382.95	330.00	0.00 Central
TRC24LU035	Bravo	658191.79 ²	1 9340365.88	5 249.945	SIRGAS2000_UTN	1_22S 257.45	330.00	0.00 Central
TRC24LU036	Bravo	658080.962	29340321.57	8 251.552	2 SIRGAS2000_UTN	1_22S 215.70	330.00	0.00 Central
TRC24LU043	Bravo	659850.13	5 9342569.58	6278.419	SIRGAS2000_UTM	1_22S 186.65	90.00	0.00 North
TRC24LU044	Bravo	659823.827	79342659.84	0272.184	4 SIRGAS2000_UTM	1_22\$ 199.35	90.00	0.00 North

Schedule 2: Assay Methodologies and QAQC

Samples follow a chain of custody between collection, processing, and delivery to the SGS laboratory in Parauapebas, state of Pará, Brazil. The drill core is delivered to the core shack at Bravo's Luanga site facilities and processed by geologists who insert certified reference materials, blanks, and duplicates into the sampling sequence. Drill core is half cut and placed in secured polyurethane bags, then in security-sealed sacks before being delivered directly from the Luanga site facilities to the Parauapebas SGS laboratory by Bravo staff. Additional information about the methodology can be found on the SGS Geosol website (SGS) in their analytical guides. Information regarding preparation and analysis of historic drill core is also presented in the table below, where the information is known.

Contact

For further information about Bravo, please visit www.bravomining.com or contact: Luis Azevedo, Chairman Alaritz Aspurate and Provide the Control of Provide the Control of Provide the Control of Internal Cartified reference materials, blanks, and duplicates. An additional QAQC program is administered by Bravo using certified reference materials, duplicate samples and blank samples that are blindly inserted internal cartified the Cartified car

Für den Inhalt des Beitrages ist allein der Autor verantwortlich bzw. die aufgeführte Quelle. Bild- oder Filmrechte liegen beim Autor/Quelle bzw. bei der vom ihm benannten Quelle. Bei Übersetzungen können Fehler nicht ausgeschlossen werden. Der vertretene Standpunkt eines Autors spiegelt generell nicht die Meinung des Webseiten-Betreibers wieder. Mittels der Veröffentlichung will dieser lediglich ein pluralistisches betrag stellen keinerlei Aufforderung zum Kauf-/Verkauf von Wertpapieren dar. Wir wehren uns gegen jede Form von Hass, Diskriminierung und Verletzung der Menschenwürde. Beachten Sie bitte auch unsere

AGB/Disclaimer! Method Method Method

Die Ranjochtkine Medifikation mer grwanding der Inhalts carre peler spilveise ohne schriftliche Genehmigung ist untersagt! Alle Angaben ohne Gewähr! Copyright © by Rohstoff-Welt de -1999-2025. Es gelten unsere AGB und Datenschutzrichtlinen.

PRPCLI (85% at 200#) FAI515 FAI30V ICP40B

SOURCE Bravo Mining Corp.

19.04.2025 Seite 5/5